

**Approx. weight**

| Material | kg | lb |
|---|---|---|
| Carbon steel | 2.9 | 6.4 |
| Stainless steel 304 and 304L | 2.9 | 6.4 |
| Stainless steel 316 and 316L | 2.9 | 6.5 |

Densities 7.85, 7.9 and 8.0 g/cm3.
Calculated from the dimensions as the standard gives them, with no allowance for tolerance.



Section



4 holes Ø22

Face view

# Hubbed threaded flange, EN 1092-1 type 13, PN 63

DN 32, facing type B1 (raised face)

Designation: Flange EN 1092-1/13/B1/DN 32/PN 63
Dimensions per EN 1092-1:2018, Table 16 (PN 63) and Table 8 (facing); tolerances per EN 1092-1.
C2 and H1 include the raised face f1, as EN 1092-1 measures it.
EN 1092-1 dimensions the hub of this type at the back face only (N2) and 5.6.2 lets it run parallel or taper up to 7 degrees; it is drawn tapering out to the pipe wall.
Thread Rp 1 1/4 to EN 10226-1 (ISO 7-1), pitch 58.6 mm: d is the major diameter, the thin line the root.
5.6.3.2 asks for no counterbore and a chamfer to the major diameter.
EN 1092-1 gives PN 63 the same dimensions as PN 100 in DN 32; only the marking differs.
Reference drawing. The purchase order and EN 1092-1 govern.
Generated at rajendradatacenter.com/flanges/en-1092-1/

| Dimension | mm | in |
|---|---|---|
| D Outside diameter | 155 | 6.10 |
| d1 Raised face diameter | 78 | 3.07 |
| f1 Raised face height | 2 | 0.08 |
| C2 Flange thickness, raised face included | 24 | 0.94 |
| H1 Length through hub, raised face included | 32 | 1.26 |
| N2 Hub diameter at back face | 68 | 2.68 |
| d Thread major diameter, Rp 1 1/4 to EN 10226-1 | 41.9 | 1.65 |
| K Bolt circle diameter | 110 | 4.33 |
| L Bolt holes, 4 off | 22 | 0.87 |

4 bolts M20; holes 22 mm (0.87 in)

RAJENDRA INDUSTRIAL CORPORATION
rajendradatacenter.com
Drawing RIC-EN1092-13-PN63-DN32-B1
Scale 1:2 on A4
Units: mm (inches)
Date 2026-11-22
Quote: rajendradatacenter.com/rfq/
sales@rajendradatacenter.com
+91 74338 71355