

Approx. weight

Material	kg	lb
Carbon steel	5.1	11.3
Stainless steel 304 and 304L	5.1	11.3
Stainless steel 316 and 316L	5.2	11.5

Densities 7.85, 7.9 and 8.0 g/cm3.
Calculated from the dimensions as the standard gives them, with no allowance for tolerance.



Section



8 holes Ø22
Face view

Hubbed threaded flange, EN 1092-1 type 13, PN 63

DN 65, facing type B1 (raised face)

Designation: Flange EN 1092-1/13/B1/DN 65/PN 63
Dimensions per EN 1092-1:2018, Table 16 (PN 63) and Table 8 (facing); tolerances per EN 1092-1.
C2 and H1 include the raised face f1, as EN 1092-1 measures it.
EN 1092-1 dimensions the hub of this type at the back face only (N2) and 5.6.2 lets it run parallel or taper up to 7 degrees; it is drawn tapering out to the pipe wall.
Thread Rp 2 1/2 to EN 10226-1 (ISO 7-1), pitch 58.6 mm: d is the major diameter, the thin line the root.
5.6.3.2 asks for no counterbore and a chamfer to the major diameter.
Reference drawing. The purchase order and EN 1092-1 govern.
Generated at rajendradatacenter.com/flanges/en-1092-1/

Dimension	mm	in
D Outside diameter	205	8.07
d1 Raised face diameter	122	4.80
f1 Raised face height	3	0.12
C2 Flange thickness, raised face included	26	1.02
H1 Length through hub, raised face included	40	1.57
N2 Hub diameter at back face	112	4.41
d Thread major diameter, Rp 2 1/2 to EN 10226-1	75.2	2.96
K Bolt circle diameter	160	6.30
L Bolt holes, 8 off	22	0.87

8 bolts M20; holes 22 mm (0.87 in)

RAJENDRA INDUSTRIAL CORPORATION
rajendradatacenter.com
Drawing RIC-EN1092-13-PN63-DN65-B1
Scale 1:2.5 on A4
Units: mm (inches)
Date 2026-11-22
Quote: rajendradatacenter.com/rfq/
sales@rajendradatacenter.com
+91 74338 71355