

Approx. weight

Material	kg	lb
Carbon steel	13.4	29.6
Stainless steel 304 and 304L	13.5	29.8
Stainless steel 316 and 316L	13.7	30.2

Densities 7.85, 7.9 and 8.0 g/cm3.
Calculated from the dimensions as the standard gives them, with no allowance for tolerance.



Section



Face view

Weldring neck, EN 1092-1 type 35, PN 25

DN 300, facing type A (flat face), neck 323.9 × 10

Designation: Collar EN 1092-1/35/A/DN 300/PN 25
Dimensions per EN 1092-1:2018, Table 14 (PN 25) and Table 8 (facing) and Annex A (wall thickness); tolerances per EN 1092-1.
Facing type A (flat face), as 5.7.2.3 gives this type unless the order says otherwise.
Collar for a type 02 loose plate flange, which bolts over it. d1 is the lap diameter and the joint face.
Reference drawing. The purchase order and EN 1092-1 govern.
Generated at rajendradatacenter.com/flanges/en-1092-1/

Dimension	mm	in
d1 Collar outside diameter	395	15.55
F35 Collar thickness	20	0.79
H4 Overall length	92	3.62
A Neck outside diameter (pipe OD)	323.9	12.75
S Neck wall thickness (min)	10	0.39
B Bore, A - 2S	303.9	11.96

RAJENDRA INDUSTRIAL CORPORATION
rajendradatacenter.com
Drawing RIC-EN1092-35-PN25-DN300-A
Scale 1:5 on A4
Units: mm (inches)
Date 2026-11-22
Quote: rajendradatacenter.com/rfq/
sales@rajendradatacenter.com
+91 74338 71355